

E-Series

Increased Reliability and Proven Design



E-Series

KUMERA E-Series

Increased Reliability and Proven Design



The E-series can be equipped with:

- Heating element
- Separate lubrication unit
- Remote condition monitoring:
Kumera Guar Gear 200

The new E- and SE-series is especially designed for demanding agitator applications in process industry.

The range comprises 15 gear models. Sizes are divided in optimum way to meet required both torque range and ratio requirements.

The maximum output torque is 840 kNm and the maximum ratio is 3550:1.

The range consists of two version options. E-version is being offered as a standard. The parallel SE-model is designed for more demanding applications.

Optimum dimensions for the housing are result of very extensive FEM-analysis.

External radial forces affecting the output shaft extension are specially taken into account when designing the housing and the output shaft and its bearings.

The parts which need to be maintained have been placed in one location to make the service operations faster and easier.

The lubrication of the bearings is always done with filtered oil to guarantee trouble free operation and maximum life time of bearings.

Pressure lubrication system is covering all bearings. The oil nozzles can be maintained without dismantling the gearbox.

The output shaft can be equipped with a key way or a fixed flange. When using a output shaft with fixed flange there is no need to have a separate coupling half.

The new E-series has two different foot mounting alternatives. One is casted structure and the other is based on steel plate which can be easily modified according to customer's need.

The sealing options for the output shaft are dry-sump, dry-well or lip seal. Dry-sump sealing is completely service free alternative. Lip seal construction is equipped with leakage oil connections.

According to customer's need the new E-series gearboxes can be delivered completely fitted with additional accessories and compatible with ATEX requirements.



| Feature | Benefits & Values |
|---|---|
| Mixer gear series with multiple sizes and ratios | Large power range of 200 – 1000 kW |
| Integrated flange coupling and output shaft | More rigid and reliable structure |
| Stronger shaft support by higher bearing span for mixer application | Higher bending load carrying capacity of the output shaft |
| Forced lubrication of all bearings | Cool, clean and filtered lubricant increase bearing reliability |
| Customized adapter plate for connection | Versatility in final assembly |
| Special ratios up to 1% of the requested ratio at moderate cost | Easy to select the optimal gear unit for a specific application value for money |
| A separate lubrication and cooling unit with an oil tank | Simple, standard systems for cooling and lubrication |
| Optimized tooth profiles using latest calculation tools | Better load distribution and lower dynamic forces reduce stresses and increase gear life |
| Case-hardened gears | A hard case and through hardened core result in a more wear resistant gear that is capable of handling even high impact loads |




POWER-PLAZA.COM

Kumera Power-Plaza is the online market place for Kumera mechanical transmission products and associated spare parts. Power-plaza.com speeds up the process of requesting for quotations. www.power-plaza.com

Other Kumera Drive Units



HELICAL GEAR UNITS,
COMPACT F-RANGE



HELICAL GEAR UNITS,
COMPACT G-RANGE



ONE STAGE HELICAL
GEAR UNITS
KUMERA LX-RANGE



HEAVY DUTY HELICAL
GEAR UNITS,
CUMERA D-RANGE



BEVEL GEAR UNITS,
COMPACT F-RANGE



BEVEL GEAR UNITS,
COMPACT G-RANGE



AGITATOR GEAR UNITS,
SG-RANGE



HEAVY DUTY AGITATOR
GEAR UNITS,
E-RANGE



WORM GEAR UNITS,
COVERA RANGE



COMBINATION HELICAL AND
WORM GEAR UNITS,
COVERA RANGE




DOUBLE WORM GEAR UNITS,
COVERA RANGE




WIND UP AND UNWIND
GEAR UNITS,
LP-RANGE



ONE STAGE HELICAL
GEAR UNITS,
CUMERA LH-RANGE



YANKEE CYLINDER
GEAR UNITS



SPECIAL GEAR UNITS



BEVEL GEAR UNITS,
KA-RANGE




FRONT END GEAR UNITS,
NORGEAR-RANGE



INTEGRATED ROLL
GEAR UNITS,
TP-RANGE



PLANETARY
GEAR UNITS,
P-RANGE



CONDITION MONITORING
GUARD GEAR 200

KUMERA POWER TRANSMISSION GROUP

KUMERA DRIVES OY

Kumerankatu 2
FI-11100 Riihimäki
FINLAND
Tel. +358 20 755 4200
Fax: +358 20 755 4220
E-mail: drives@kumera.com

KUMERA AS

P.O. Box 2043
N-3202 Sandefjord
NORWAY
Tel. +47 33 48 54 54
Fax: +47 33 48 54 55
E-mail: sales@kumera.no

KUMERA ANTRIEBSTECHNIK GMBH

Raiffeisenstrasse 38-40
A-8010 Graz
AUSTRIA
Tel. +43 316 471 524-0
Fax: +43 316 462 550
E-mail: kumera.graz@kumera.com



KUMERA (CHINA) CO, LTD.

168 Meifeng Road
Kunshan 215300, Jiangsu
CHINA
Tel. +86 512 503 61701
Fax: +86 512 503 61710
E-mail: kumerachina@kumera.com